

DATA SYSTEMS



SPARTE 500 L/S/C

Tracking Antennas
15ft (4.6m) / 18ft (5.5m)



TELEMETRY GROUND SOLUTIONS

SPARTE 500 series antenna, commonly mounted with a 5.5m reflector, is a field and time proven product delivered to customers for **mission-critical applications** where the telemetry reception is at stake.

Wherever telemetry tracking and reception matters, Safran Data Systems SPARTE 500 series antennas make the difference: **high performance, upgrade-ability to C-band support, skid, container or trailer-mounted mobility, and even 3-axis shipborne versions.**

Widely used across world test ranges, the SPARTE 500 series antennas **meet the most demanding flight test profiles.** Its lean design and ease of operations make it a perfect match for **any ground test range**, as a complement to smaller range trackers.



Launch Vehicle Telemetry



Missile Testing



Fixed & Rotary Wing

BEST-IN-CLASS SERVO CONTROLS

User Selectable Servo Controls

SCM 1000HZ SCAN RATE

Common SCM Design for Main & ACQ-AID Antenna

MODULAR L, S OR C BAND

Simple Add-On upgrade without any Structural Change

TIME PROVEN

Robust Pedestal in Operations at Test Sites for Decades

TRANSPORTABLE ADAPTATION KIT

Skid, container or Trailer-Mounted Versions

TELEMETRY GROUND SOLUTIONS

SPARTE 500 L/S/C

SYSTEM SPECIFICATIONS

Pedestal

Azimuth Travel Range Unlimited
 Elevation Travel Range -5° / + 185°
 (option -15 / +195°)
 Angular Velocity 20°/s
 Angular Acceleration 20°/s²
 Motors Single Drive DC Brushless

Reflector

8 Panel Segmented Auto-Aligned Carbon Fiber

Servo-Control

Pointing Accuracy ≤ 0.1°
 Tracking Accuracy ≤ 0.1°
 Acceleration Lag 0.07°/s²

Antenna Control Unit

Manual, Slew, Scan, Slave (2 x Inputs), RF Tracking, Program-Track, GPS Slaving

Advanced Features: Autotracking (Automatic ACU Modes Management), Auto Acquisition (with Adjustable Signal Thresholds), Multipath Clipping, Phase & Slope Auto Calibration, ...

Tracking Signal Inputs 4x Pairs of AM+AGC and tracking over IP
 Auto-Diversity LHCP/RHCP, Best Telemetry Channel
 Diagnostic Tool Continuous BIT, Servo-Control, Tracking, Y-Factor, Logbook, Parameters Recording

General Characteristics

Power 400 Vac 50-60Hz. 6.8kVA
 Antenna Weight 3000 - 3300 kg (6610 - 7275 lbs) depending of the configuration

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature Range

Outdoor Equipment -20°C to +45°C (-4°F to 113°F)
 Indoor Equipment +10°C to +35°C (+50°F to +95°F)

Humidity

Outdoor 100 %
 Indoor 85 % Non-Condensing

OPTIONAL ITEMS

- ▶ Operator control desk
- ▶ Video camera for visual target aiming
- ▶ Single/Dual/Tri-band feed
- ▶ 4.60m / 5.50m reflector
- ▶ SCM feed up to 1000 Hz tracking rate
- ▶ Acquisition aid feed
- ▶ Low gain switching for short range
- ▶ Skid or Trailer mounted version
- ▶ GPS time / position / heading synchronization (single or differential)
- ▶ Shipborne version with Inertia Measurement Unit (IMU) and -15° lower El limit
- ▶ 3-axis version
- ▶ Range control with TM Maestro
- ▶ Extend temperature range

OPTIONS ON REQUEST

- ▶ Long loop test capability with 3 channel rotary joint
- ▶ Improved G/T
- ▶ Radome environment protection

	4.6 M / 15 FT	5.5 M / 18 FT
Tracking	8 Dipoles Monopulse	
Receive Frequency Range	1435 - 1545 MHz / 1790 - 1850 MHz / 2200 - 2400 MHz / 4400 - 5250 MHz	
Receive Polarization	RHCP and LHCP	
3dB Beamwidth @ 2.3GHz	2°	1.6°
G/T @2300 MHz, No Filter, 25° Elevation, 20°C Clear Sky	14.5 dB/K	16 dB/K
Maximum Wind for Nominal / Degraded Performance / Survival	100 / 120 / 200 km/h	85 / 100 / 200 km/h



GLOBAL SALES

5, Avenue des Andes - CS 90101 - 91978 Courtaboeuf Cedex - FRANCE - Tel.: +33 1 69 82 78 00 - Email: sales.sdsy@safrangroup.com

USA

3005 Business Park Dr - Norcross, GA 30071 - USA - Tel.: +1 770 753 4017 - Email: sales@SafranDataSystemsUS.com

